



# Tron SART20

RADAR TRANSPONDER



[www.jotron.com](http://www.jotron.com)



# ▶ Tron SART20

## RADAR TRANSPONDER

Tron SART20 is designed for use in search and rescue (SAR) operations. A radar transponder gives the location for any nearby vessel and aircraft with X-band radar. Radar transponder is designed for use in lifeboats and liferafts. Easy mounting in bulkhead bracket onboard the vessel, easy to release and activate in an emergency situation. Various installation devices available as options. MED and other approvals available. Mandatory carriage equipment for all ships of 300 gross tonnage and upwards, according to SOLAS III/6.2.2, III/26.2.5 and IV/7.1.3.



Bulk head bracket  
Lifeboat bracket  
Pole bracket  
Life raft mounting strap

**Agent/Distributor:**

Jotron AS reserves the right to change the design and/or specifications at any time without prior notice. Reservations are also taken towards any general errors that may occur.

v.B

[www.jotron.com](http://www.jotron.com)

### SPECIFICATIONS

TECHNICAL	
Weight	482 g
Height:	251 mm (9 7/8")
Material housing:	Glass-reinforced Polycarbonate
Frequency	X-band (3 cm) (9.2 - 9.5 GHz)
Radiated power	> 400 mW e.i.r.p (+26 dBm)
Sweep type	12 sweep sawtooth type Forward 7.5 $\mu$ s $\pm$ 1 $\mu$ s Return 0.4 $\mu$ s $\pm$ 0.1 $\mu$ s starts with return sweep
Receive sensitivity	Better than -50 dBm e.r.s
Response delay	Max 0.5 $\mu$ s
Antenna pattern	Horizontal polarisation Omnidirectional radiation in the horizontal plane Greater than $\pm$ 2.5 degrees elevation angle in the vertical plane
Antenna height	Place at least 1m (3.3 ft) above sea/ground level
Indication	Visual and audible alarm
Temperature range	Operating: -20°C to +55°C Storage: -30°C to +65°C
Battery	Lithium, non hazardous battery for safe and unrestricted transportation 5 year maintenance kit, serviceable on board
Operating life	96 hours standby + 8 hours continuous operation when activated by a radar with 1 kHz prf at -20°C.
Standards	IEC 61097-1 IEC 60945 IMO A.802 (19) IMO A.694 (17) MSC.247(83)
ACCESSORIES	
Brackets	Bulkhead bracket Lifeboat bracket
For life raft	Life raft mounting pole Neoprene bag and strengthened lanyard Life raft mounting strap
WARRANTY	
	5 years

### CONTACT INFORMATION

Jotron AS  
P.O.Box 54  
3281 Tjodalving  
Norway  
Tel: +47 33 13 97 00  
Fax: +47 33 12 67 80  
sales@jotron.com

Jotron UK Ltd.  
Crosland Park  
Cramlington  
NE23 1LA  
United Kingdom  
Tel: +44 (0) 1670 712000  
Fax: +44 (0) 1670 590265  
sales@jotron.com

Jotron Asia Pte. Ltd.  
19 Loyang Way  
Changi Logistics Centre  
Rear Office Block 04-26  
Singapore 508724  
Tel: +65 65426350  
Fax: +65 65429415  
sales@jotron.com

Jotron USA, Inc.  
10645 Richmond Avenue, Suite 170  
Houston, TX 77042  
USA  
Tel: +1 713 268 1061  
Fax: +1 713 268 1062  
sales@jotron.com